

KITCHEN EQUIPMENT

CT1650+ SYSTEM

Advantages of the Merlin CT1650+ System

- Unique internal visual display showing the fan current.
- Allows Compliance with BS6173 for commercial kitchens.
- To be used when all appliances have flame failure devices.
- 2 built in current monitors can be easily calibrated to suit any fan.
- Reliable method of interlock, with no moving parts there is little to go wrong.
- BMS and fire alarm interface.
- Will accept remote and emergency knock-off buttons
- Can monitor up to 0.1 to 18 amp running current (per fan monitor)
- Carbon Dioxide detectors accepted.
- Calibration ranges to cover a wide variety of fans.
- Covered by S&S Northern Ltd 3-year warranty.




Complete piece of mind in a single panel

The Merlin 1650+ is able to work in conjunction with a Merlin Carbon Dioxide detector. If a Carbon Dioxide detector is fitted and a pre-determined level of CO2 is detected, a signal will be sent to the 1650+ panel which will send the panel into alarm and close the gas solenoid valve. The valve cannot be reset until the CO2 reaches an acceptable level.

The Merlin 1650+ can be interfaced with building management systems and fire alarm systems to isolate the gas supply in event of a fire.

S&S Northern Ltd has a full technical team available on 01257 470 983. Call Now!



Merlin CT1650+ Box Dimensions

Height	178mm
Length	254mm
Depth	62mm

S&STM
NORTHERN
www.snsnorthern.com