



**Gas, Water & Air Controls
 Product Catalogue**

GAS SAFETY IN EVERY ENVIRONMENT.

**The UK's leading designer, manufacturer and supplier of
the latest range of gas safety products.**

Ranges include; gas ventilation and gas interlock systems for use in commercial kitchens, gas pressure proving systems and gas detection systems for school laboratories and boiler houses.
Designed and manufactured in the UK.



40+ Years Industry Experience



Easy to Install Solutions



3 Year Product Warranty



24/7 Tech Back Up



Fully Trained Sales Engineers



Express Delivery Available

Office information

For your local sales manager contact S&S Northern Ltd



Head Office
 S&S Northern Ltd
 Wallace Francis House
 Barnes Wallis Way
 Buckshaw Village
 Chorley
 Lancashire
 PR7 7JN

T +44 (0) 1257 470 983
 E info@snsnorthern.com

Contents



KITCHEN



SCIENCE LAB



BOILER ROOM

8-9. Kitchen Introduction

- 10. **3000S** Energy Saving Demand Controlled Ventilation System
- 11. **CT1750** Solid Fuel Gas Safety System
- 12. **CT1650+** Intelligent Current Monitoring Interlock System
- 13. **CT1250X** Intelligent Current Monitoring Interlock System
- 14. **CT1200S** Gas Interlock System (2 Fan Inputs)
- 15. **2000X** Gas Proving & Current Monitoring System (4 Fan Inputs)

16-19. Science Lab Introduction

- 20. **1000VW+** Gas Proving, Electric & Water Isolation, Fan Interlock
- 21. **1000V+** Gas Proving & Electric Isolation, Fan Interlock
- 22. **1000V** Gas Proving, Fan Interlock

24-25. Boiler Room Introduction

- 26. **GDPX+** Gas Proving & Detection with remote monitoring (16 Zone)
- 27. **GDP2X** Gas Detection (2 Zone)
- 28. **1000BH** Gas Proving & Detection (2 Zone)
- 29. **GDP2** Gas Detection (2 Zone)
- 30. **500S** Utility Isolation Panel



DETECTORS



WATER LEAK



ANCILLARIES

32-33. Detectors Introduction

- 34. **Detector IS** Gas Detector for BMS integration (Screen)
- 35. **Detector I** Gas Detector for BMS integration (No Screen)
- 36. **Detector** Gas Detector GDP
- 37. **Detector X** Gas Detector X
- 38. **CO2-X** Carbon Dioxide Monitor (Screen)
- 39. **RS Range** Carbon Dioxide, Temperature & Humidity
- 40. **CO2 Desktop White** Air Quality Monitor
- 40. **CO2 Desktop Black** Air Quality Monitor
- 41. **CH4CO TFT Mini Merlin** Combined Natural Gas & Carbon Monoxide Monitor

42-43. Water Leak Introduction

- 44. **Cold Water Meter**
- 44. **Hot Water Meter**
- 44. **PIR Sensor**
- 45. **Merlin WDP** Major Water Leak Monitoring System
- 45. **Merlin Water Check** Combined Flow Monitoring & Point Detection System
- 46. **Merlin WLM** Water Leak Detection System
- 46. **Merlin WLMCP** Puck / Probe
- 47. **Merlin WLMC** 2 Core Sensing Cable
- 47. **Merlin WLMFC** 4 Core Sensing Cable With Fault Detection

48-49. Ancillaries Introduction

- 50. **FAB-1** Fire Alarm Bypass
- 50. **Emergency Stop** Break Glass Emergency Knock-Off Button
- 51. **Fusible Link** Heat Detector (Audible & Visual)
- 51. **Sounder Alarm Beacon**
- 52. **Air Pressure Switch**
- 52. **Gas Solenoid Valve**
- 53. **Water Solenoid Valve**
- 53. **Gas Proving Transmitter**
- 54. **DPM2** Dual Gas Pressure Transmitter Module
- 54. **PM2+** Intelligent Dual Current Monitor
- 55. **CS1/CS2** Dual Current Monitor
- 55. **Optical Sensor** Canopy Mounted Smoke/Steam Sensor

- 56. **Duct Thermostat** Duct Mounted Temperature
- 56. **Invertor** Single Phase & Three Phase
- 57. **Speed Controller** Single Phase
- 57. **Gas Meter** In-Line
- 58. **Water Meter**
- 58. **Heat Meter**
- 59. **CPI Switch** For Gas Solenoid Valves
- 59. **Bump Test Kit**



INDOOR AIR QUALITY

*\$-% 7 cblfc`g Introduction

- * &^FG^Fub[Y Ôçàà[] Ôç cã^E
- V^ [] ^!æ !^B^R { ææ
- 63. **IAQ Range** Ôçàà[] Ôç cã^E
- V^ [] ^!æ !^, P^ { ææ, PM1, PM2.5, PM10 & VOCs
- 64. **RG Range** VRF Refrigerant Gas Leak Detection

Product key features

The benefits of each of our products are illustrated in an icon format throughout this brochure, aiding you to select the product and design features most suited for your requirements.

The icons are located at the top of each product page with accompanying detail for ease of reference and comparison of the solutions we have available.

If you have any questions about any products and their features please contact info@snsnorthern.com.



Kitchens

S&S Northern have a range of gas interlock and environmental monitors to meet all of the latest gas and ventilation regulations for commercial kitchens. We have industry leading range of products, from a simple gas interlock system to our advanced demand controlled kitchen ventilation systems and environmental monitors.



PAGES
8-15

Merlin 3000S System



ENERGY SAVING
DEMAND
CONTROLLED
VENTILATION
SYSTEM



The Merlin 3000S energy saving system is a combined demand controlled ventilation system with built in gas interlock and optional gas proving.

The 3000S system automatically adjusts the speed of the ventilation based on the kitchen environment.

The ventilation is automatically controlled based on the carbon dioxide levels, smoke/steam present in the canopy, carbon monoxide, real time gas usage and temperature.

This system can offer large financial savings and short payback periods for any commercial kitchen.

Additional features

Saves energy by varying the ventilation speed via 0-10v DC output. This reduces manual ventilation control.

OFTEN
USED
WITH

Gas Solenoid
valve
Page 50

PM2+ Current
Monitor
Page 52

CO2-X
Page 38

Carbon
Monoxide
detectors
Page 32

Optical Sensor
Page 53

Duct
Thermostat
Page 54

TBX Gas Meter
Page 55

Inverter
Page 54

*Please note before ordering the ventilation system / inverter must accept a 0-10v DC control signal.

Merlin CT1750 System



OFTEN
USED
WITH

Gas Solenoid
valve
Page 50

PM2+ Current
Monitor
Page 52

CO2-X
Page 38

Carbon
Monoxide
detectors
Page 32

Inverter
Page 54



The Merlin CT1750 System is a gas interlock and manual ventilation control system designed for commercial kitchens. The Merlin CT1750 System comes with two variable fan speed controllers (0-10V output) to control the speed of 2 fans via an inverter.

The Merlin CT1750 System works with carbon dioxide monitors and carbon monoxide detectors to increase the speed of the ventilation when these gases are present, both in and out of working hours.

*Please note before ordering the ventilation system / inverter must accept a 0-10v DC control signal.

Commonly used in kitchens with solid fuel appliances.

Additional features

Can control the ventilation via 0-10V output.

*Transmitter supplied separately

SOLID FUEL
GAS SAFETY
SYSTEM

Merlin CT1650+ System



Monitor up to four fans

Built in LCD current monitors

Suitable with both single phase and three phase fans

Designed to BS6173 & IGEM/UP19 standards

Fire Alarm Input & BMS output

INTELLIGENT CURRENT MONITORING INTERLOCK SYSTEM



The Merlin CT1650+ System is a current monitoring interlock system for commercial kitchens. This comes with two built in intelligent current monitors.

The Merlin 1650+ has the facility to interlock with two additional fans via remote current monitors PM2+ / CS1-2) or air pressure differential switches. The 1650+ is commonly used with a carbon dioxide monitor.

Additional features

- Intelligent Current Monitors to set "high" and "low" parameters.
- Current Monitors parameters 0.2amp to 20amp.
- Adjustable sensitivity threshold to reduce nuisance drop outs.
- Fan start stop output (12v output when on).

OFTEN USED WITH

Gas Solenoid valve
Page 50

CO2-X
Page 38

Emergency Stop
Page 48

Speed Controller
Page 55

Merlin CT1250X System



Ventilation control for up to two fans

Built in LCD current monitors

Suitable with both single phase and three phase fans.

Designed to BS6173 & IGEM/UP19 standards

Fire Alarm Input & BMS Output

OFTEN USED WITH

Gas Solenoid valve
Page 50

Emergency Stop
Page 48

Speed Controller
Page 55



The Merlin CT1250X System is a current monitoring interlock system for commercial kitchens. This comes with two built in intelligent current monitors.

The Merlin CT1250X has the facility to interlock with two additional fans via remote current monitors (CS1-2) or air pressure differential switches.

Additional features

- Intelligent Current Monitors to set "high" and "low" parameters.
- Current Monitors parameters 0.2amp to 18amp.
- Adjustable sensitivity threshold to reduce nuisance drop outs.

CURRENT MONITORING INTERLOCK SYSTEM

Merlin CT1200S System

- 
Monitor up to two fans
- 
Integral Emergency Stop
- 
Designed to BS6173 & IGEM/UP19 standards
- 
Fire Alarm Input & BMS output

**GAS INTERLOCK SYSTEM
(2 FAN INPUTS)**







The Merlin CT1200S System is a gas interlock system for commercial kitchens. This can monitor ventilation using air pressure differential switches or external current switches.

Additional features

- Facility to interlock using current switches or air pressure differential switches.
- 10 Second Nuisance Tripping Delay

- OFTEN USED WITH**
- Gas Solenoid valve **Page 50**
 - Air Pressure Differential Switch **Page 50**
 - Emergency Stop **Page 48**
 - Speed Controller **Page 55**

Merlin 2000X System

- 
Monitor up to four fans
- 
Built in LCD current monitors
- 
Gas proving feature*
- 
Designed to BS6173 & IGEM/UP19 standards
- 
Fire Alarm Input & BMS Output
- 
External gas detector

- OFTEN USED WITH**
- Gas Solenoid valve **Page 50**
 - Merlin CO2-X **Page 38**
 - Merlin Gas Detectors **Page 32**
 - PM2+ Current Monitor **Page 52**
 - Air Pressure Differential Switch **Page 50**



The Merlin 2000X is a ventilation interlock and gas proving system for commercial kitchens and includes two built in intelligent current monitors.

The Merlin 2000X comes with a gas pressure transmitter included for commercial kitchens where gas appliances don't have lame failure devices. The Merlin 2000X System works with external current monitors or air pressure differential switches, the system can also interface with various gas detectors.

Additional features

- Intelligent Current Monitors to set "high" and "low" parameters.
- Current Monitors parameters 0.2amp to 20amp.
- Adjustable sensitivity threshold to reduce nuisance drop outs.
- Fan start stop output (12v output when on).
- Facility to interlock using external current switches or air pressure differential switches (4 fans)
- Works with gas detectors and Carbon monoxide monitors
- *Transmitter included

**GAS PROVING SYSTEM
(4 FAN INPUTS)**

Science Lab


S&S Northern have a range of gas proving systems for educational establishments. Our systems protect Laboratories, food tech and design tech classrooms. We also have products that protect laboratories that have speciality or high pressure gases.



PAGES
16-23

**COMPACT,
ROBUST &
RELIABLE**

Gas pressure proving systems



- ✓ Incredibly easy to use and install
- ✓ Adjustable time out facility
- ✓ Industrial grade polycarbonate material to withstand daily use
- ✓ Meets IGEM/UP11

1. Modern design

Slim compact enclosure

2. Clear status indication

For each utility

3. Quick operation

Keyed authority ON/OFF Alarm reset

4. Robust control

Touch sensitive buttons







5. Ease of access

Power indication and QR code for easy access to manuals

6. Emergency stop button

Recessed panic button eliminates accidental shut down

Merlin 1000 VW+

- 
Ventilation interlock
- 
Integral Emergency Stop
- 
Isolates gas, water and electric (via contactor)
- 
Designed to IGEM/UP11 standards
- 
Fire Alarm Input & BMS Output
- 
Gas proving feature*

GAS PROVING,
ELECTRIC
& WATER
ISOLATION, FAN
INTERLOCK



The Merlin 1000VW+ gas pressure proving, electric and water isolation system is designed specifically for use in educational buildings and Laboratories. The 1000VW+ can also interlock any mechanical ventilation.







Additional features

- Facility to interlock with the ventilation units.
- Gas valve output
- Low Pressure Monitoring for incoming gas supply
- Works with Carbon Dioxide Monitor

*Gas pressure transmitter included

- OFTEN USED WITH
- Gas Solenoid valve
Page 50
 - Water Solenoid Valve
Page 51
 - Merlin CO2-X
Page 38
 - Air Pressure Differential Switch
Page 50

Merlin 1000V+

- 
Ventilation interlock
- 
Integral Emergency Stop
- 
Isolates gas and electric (via contactor)
- 
Designed to IGEM/UP11 standards
- 
Fire Alarm Input & BMS Output
- 
Gas proving feature*

- OFTEN USED WITH
- Gas Solenoid valve
Page 50
 - Merlin CO2-X
Page 38
 - Air Pressure Differential Switch
Page 50
 - Emergency Stop
Page 48



The Merlin 1000V+ gas pressure proving and electric isolation system is designed specifically for use in educational buildings and Laboratories with ventilation interlocking between the ventilation system and the gas solenoid valve. The system is compatible with external current monitors or air pressure differential switches in order to interlock with the ventilation units.

Additional features

- Facility to interlock with ventilation units.
- Gas valve output
- Low Pressure Monitoring for incoming gas supply
- Works with Carbon Dioxide Monitor

GAS PROVING,
ELECTRIC
ISOLATION, FAN
INTERLOCK

Merlin 1000V



Ventilation
interlock



Integral
Emergency
Stop



Designed to
IGEM/UP11
standards



Fire Alarm
Input & BMS
Output



Gas proving
feature*

GAS
PROVING, FAN
INTERLOCK



The Merlin 1000V+ gas pressure proving system is designed specifically for use in educational buildings and Laboratories with ventilation interlocking between the ventilation system and the gas solenoid valve. The system is compatible with external current monitors or air pressure differential switches in order to interlock with the ventilation units.

Additional features

- Facility to interlock using current switches or air pressure differential switches (4 fans)
- Gas valve output
- Low Pressure Monitoring for incoming gas supply
- Works with Carbon Dioxide Monitor

*Gas pressure transmitter included

OFTEN
USED
WITH

Gas Solenoid
valve
Page 50

Merlin CO2-X
Page 38

Air Pressure
Differential
Switch
Page 50

Emergency
Stop
Page 48





Boiler Room

S&S Northern have a solution for every commercial Plant room application. We offer a wide range of control panels, gas detectors, heat sensors and gas solenoid valves. Whether your project is a small residential application or a large scale plant room we have the knowledge and experience to offer the perfect products. Remote monitoring, Modbus and data logging are available on our GDPX Range.

PAGES
24-31

Merlin GDPX+



Remote monitoring LAN connection



Integral Emergency Stop



Meets all latest standards



In built fire alarm bypass mode




Gas proving feature*



Connections for BMS and Modbus outputs

GAS PROVING & DETECTION WITH REMOTE MONITORING (16 DETECTORS)



The Merlin GDPX+ is a multi-zone gas detection panel which can be used in many applications such as boiler house/ Plant rooms, factories, car parks and high rise. It can be used with up to 16 Merlin gas detectors for monitoring and detecting gas including carbon monoxide, LPG, Natural Gas, Oxygen and Hydrogen.

The GDPX+ can be remotely monitored from www.snsnorthern.com so you can monitor the status of your sites from your computer or smartphone.

Additional features

- Internet enabled (LAN)
- Remote monitoring LAN connection using snsnorthern.com portal
- Can be used with up to 16 gas detectors
- Connections for heat detectors/thermal links
- Two spare Input Connections (for additional detectors, fans, equipment)

*Gas pressure transmitter included

OFTEN USED WITH

Gas Solenoid valve
Page 50

Natural Gas – X Detector
Page 37

Carbon Monoxide – X Detector
Page 37

LPG – X Detector
Page 37

Fusible Link
Page 49

Emergency Stop
Page 48

Merlin GDP2X



Integral Emergency Stop



Meets all latest standards



Fire alarm input



Connections for heat detectors/thermal links

OFTEN USED WITH

Gas Solenoid valve
Page 50


Natural Gas – X Detector
Page 37

Carbon Monoxide – X Detector
Page 37

LPG – X Detector
Page 37

Fusible Link
Page 49

Emergency Stop
Page 48



The Merlin GDP2X is a 2 zone gas detection panel it can be used with up to 8 Merlin gas detectors (model X) for monitoring and detecting gas including carbon monoxide, LPG, Natural Gas, Oxygen and Hydrogen.

Additional features

- Gas valve output
- Can be used with up to 8 gas detectors
- Connection for sounder/strobe

**GAS
DETECTION
(8 DETECTORS)**

Merlin 1000BH



Integral
Emergency
Stop



Meets all latest
standards



Gas proving
feature*



Connections for
heat detectors/
thermal links



Integral
Emergency
Stop



Meets all latest
standards



Connections for
heat detectors/
thermal links

Merlin GDP2

GAS PROVING & DETECTION (2 ZONE)



The Merlin 1000BH is a gas pressure proving and gas detection panel for use in plant rooms and boiler houses. This panel is to be used to carry out a gas proving test on the pipe work in order to highlight if there is a gas appliance open or a gas leak. The Merlin 1000BH is designed to give the user full control over the incoming gas supply with the lockable keyswitch operation.

Additional features

- Gas valve output
- Can be used with two gas detectors
- Connections for BMS

*Gas pressure transmitter included

OFTEN USED WITH

Gas Solenoid
valve
Page 50

Natural Gas
Detector
Page 36

Carbon
Monoxide
Detector
Page 36

LPG
Detector
Page 36

Fusible Link
Page 49

Emergency
Stop
Page 48

OFTEN USED WITH

Gas Solenoid
valve
Page 50

Natural Gas
Detector
Page 36

Carbon
Monoxide
Detector
Page 36

LPG
Detector
Page 36

Fusible Link
Page 49

Emergency
Stop
Page 48



The Merlin GDP2 is a two zone gas detection panel which can be used in many applications such as factories, car parks, shopping centres and most commonly - boiler houses.

Additional features

- Gas valve output
- Can be used with up to 6 gas detectors
- Connections for BMS
- Connection for sounder/strobe

GAS DETECTION (2 ZONE)

Merlin 500S



Clear digital display for system indications



Meets all latest standards



Connections for heat detectors/thermal links

UTILITY ISOLATION PANEL



The Merlin panel is designed to provide the user with an effective means of isolating the utility, via a key switch or in the event of an emergency, by operation of the emergency shut off button. The 500S has a fascia mounted emergency shut off button fitted as standard and the fascia mounted LEDs give simple and concise information to the operator. The panel is fully compatible with S&S Northern remote emergency stop terminals allowing a large number of emergency terminals to be connected in series and wired back to the panel.

Additional features

- Easy installation
- Covered by S&S Northern Ltd 3 year warranty

OFTEN USED WITH

Gas Solenoid valve
Page 50

Fusible Link
Page 49

Emergency Stop
Page 48



Detectors

S&S Northern manufacture a wide range of gas detectors for monitoring air quality, toxic gases, explosive and flammable gases. They are designed to be easy to install and maintained. Each target gas has unique characteristics and therefore the detector needs to be installed to suit the target gas, please contact us or have a look on our website for mounting height information and advice on installation.



PAGES
32-41

Detector-iS



Clear digital display



Automatic alarm



24VAC/DC powered.



Fan controller enabled relay output



Traffic Light Indication Display



Automatic alarm



24VAC/DC powered.



Fan controller enabled relay output

GAS DETECTOR WITH VARIABLE OUTPUTS SUITABLE FOR BMS INTERFACE - TFT SCREEN



The Detector iS range is used in various applications such as boiler/ plant rooms, hospitals, laboratories and high rise buildings. These sensors are specifically built to work with all Merlin control panels and can also be used direct with BMS control panels.

The clear digital display allows the user to clearly see the current gas levels and the traffic light indicator will summarise the gas levels - Green Safe, Yellow - Attention, Red - Danger

Gases Available:

Natural Gas, Carbon Monoxide, LPG, CO₂, Oxygen, NO₂, Hydrogen, Refrigerant

Additional features

- 24VAC/DC
- PPM/LEL on TFT screen with Traffic Light Colours
- Audible Alarm
- 2 x Relay Output: 1 x Pre Alarm, 1 x Alarm
- 1 x CL Connection for GDP Range
- 0-10V output linear scale to full range
- End of Life Reminder

CO₂ Version available as above with the following additions:

- 1 x Dipswitch to change linear 0-10V output between 2 ranges: 1-2000ppm and 0-5000ppm
- 2 x Dipswitches for Alarm Settings - 1000ppm, 1500ppm, 2800ppm and 4500ppm.
- 1 x Dipswitch for Audible Alarm On/Off
- 1 x Dipswitch - Latching - Enable / Disabled

Detector-i



The Detector i range is used in various applications such as boiler/ plant rooms, hospitals, laboratories and high rise buildings. These sensors are specifically built to work with all Merlin control panels and can also be used direct with BMS control panels.

The traffic light indicator will summarise the gas levels – Green Safe, Yellow - Attention, Red - Danger

Gases Available:

Natural Gas, Carbon Monoxide, LPG, CO₂, Oxygen, NO₂, Hydrogen, Refrigerant

Additional features

- 24VAC/DC
- Traffic Light Indication
- Audible Alarm
- 2 x Relay Output: 1 x Pre Alarm, 1 x Alarm
- 1 x CL Connection for GDP Range
- 0-10V output linear scale to full range
- End of Life Reminder

CO₂ Version available as above with the following additions:

- 1 x Dipswitch to change linear 0-10V output between 2 ranges: 1-2000ppm and 0-5000ppm
- 2 x Dipswitches for Alarm Settings - 1000ppm, 1500ppm, 2800ppm and 4500ppm.
- 1 x Dipswitch for Audible Alarm On/Off
- 1 x Dipswitch - Latching - Enable / Disabled

GAS DETECTOR WITH VARIABLE OUTPUTS SUITABLE FOR BMS INTERFACE - WITHOUT SCREEN

Detector

- 
 Traffic Light
 Indication Display
- 
 Designed to
 ISEM/UP11
 standards
- 
 Low voltage
 input



**GAS DETECTOR
WITH VFC OUTPUT**

The Detector range are used in various applications such as boiler/plant rooms, hospitals, laboratories and high rise buildings.

These sensors are specifically built to work with all Merlin control panels and can also be used direct with BMS control panels.

The traffic light indicator will summarize the gas levels:

- Green - Safe
- Yellow - Attention
- Red - Danger

Gases Available:
 Natural Gas, Carbon Monoxide, LPG, CO2, Oxygen, NO2

Additional features

- 24VAC/DC
- Audible Alarm
- 1 x VFC at High Level Alarm
- 1 x CL Connection for GDP Range

- 
 Clear digital
 display with
 traffic light
 feature
- 
 Automatic
 alarm
- 
 24VAC/DC
 powered.

Detector X



**GAS DETECTOR
WITH VFC OUTPUT -
WITH SCREEN**

The Detector X range are used in various applications such as boiler/plant rooms, hospitals, laboratories and high rise buildings.

These sensors are specifically built to work with all Merlin control panels and can also be used direct with BMS control panels.

The traffic light indicator will summarize the gas levels:

- Green - Safe
- Yellow - Attention
- Red - Danger

Gases Available:
 Natural Gas, Carbon Monoxide, LPG, CO2, Oxygen, NO2, Refrigerant

Additional features

- 24VDC
- Traffic Light Indication
- Audible Alarm
- 1 x Relay Output – 1 x Alarm
- 1 x CL Connection for GDP Range
- MODBUS Output
- Calibration Service and End of Life Reminder

CO2-X Monitor



Clear digital display



Designed specifically for BB101



Automatic alarm



12V DC, 24VDC or 230V AC powered.



Fan controller enabled relay output



CARBON
DIOXIDE
MONITOR

The CO2-X is a dual powered carbon dioxide and temperature monitor, which has the ability to show average readings over an 8 hour period.

Additional features

- Can automatically change alarm settings based on gas valve activation
- CO2 and temperature levels measured and displayed clearly.

- 2 x 0-10V Signal output.
- Displays average readings of CO2 concentration over an 8 hour period.
- End of life and fault notifications.
- Pre alarm and alarm output.
- Variable CO2 and temperature output



Analog or Digital Communications



Designed to IGEN/UP11 & Part F standards



Mains or 24V Powered

Merlin RS Series



CARBON DIOXIDE,
TEMPERATURE &
HUMIDITY ROOM
SENSORS

Monitor and measure carbon dioxide (CO2), temperature and relative humidity. Designed for all areas being directly connected to low or mains voltage supply, e.g., residential, public, commercial, and light industrial environments.

Key Features

- Analog: 3x 0-10V signals for CO2 (PPM), Temperature (°C) and Humidity (% Relative).
- Digital RS-485: Modbus RTU or BACnet MS/TP communication protocols.
- VFC Relay (CO2): 1x SPST 70mA Max.
- 10K3 Thermistor output for 3rd party temperature monitoring.

Merlin IAQ Monitor

CO₂, Temperature, Humidity, PM1, PM2.5, PM10 & VOC's



Monitor and measure carbon dioxide (CO₂), temperature, dust (PM), volatile compounds (VOCs) and relative humidity. Designed for all areas being directly connected to mains or low 24v AC or DC voltage supply, e.g., residential, public, commercial, and light industrial environments, which support a Digital RS-485: Modbus RTU or BACnet MS/TP communication protocols.

See further details on page

Additional features

- Digital RS-485: Modbus RTU or BACnet MS/TP communication protocols
- 110V or 24VAC/DC power input
- Meets WELL performance & RESET standards



Merlin RG

VRF Refrigerant Gas Leak Detector



Introducing the Merlin RG, our cutting-edge Refrigerant Leak Detector designed for use with VRF (variable refrigerant flow) systems.

Meticulously designed for a diverse array of environments spanning residential, commercial, and light industrial sectors. Engineered with precision and reliability in mind, our detectors ensure unparalleled performance and safety in spaces such as hotel rooms, apartments, food retailers, and offices with premium NDIR sensing technology. Including Bacnet, 0-10V & relay outputs.

See further details on page

Additional features

- Analog: 1x 0-10V signals for refrigerants (PPM).
- Digital RS-485: BACnet MS/TP communication protocols.
- Over 40+ refrigerant gases available.
- Thermistor output for 3rd party temperature monitoring.
- Excellent stability and strong anti-interference, long-life sensors.
- Fully calibrated.
- Standard 3 year manufacturers warranty.
- In-built audible alarm
- Visual LED for alarm status



Clear digital display with traffic light feature



Mains powered or 24VDC



Gas Level Indicator for both NG and CO

Mini Merlin CH4CO TFT



The Mini Merlin CH4CO TFT for domestic applications.

The Mini Merlin CH4CO TFT is a dual gas sensor carefully designed and tested to monitor levels of natural gas- Methane (NG) and Carbon Monoxide (CO) in the air. If there is a dangerous build-up of gas or unsafe levels of carbon monoxide at the sensor, this device can shut off the gas supply via a gas safety valve.

Additional features

- Dual sensor built into one controller
- End of life notification
- Shuts off gas when in high alarm
- Low voltage input to connect with emergency stops and fire alarms.
- Pre alarm and alarm output
- LPG & CO detector available

COMBINED
NATURAL GAS &
CARBON MONOXIDE
DETECTOR

Water Leak Detection

S&S Northern have a wide a range of water leak detection & control systems, including major water leak to achieve BREEAM 1.0 2018, permanent water leak, designed for rope & puck sensors and motion controlled water supplies for toilet areas.



PAGES
42-47

Water Meters



S&S offer a large range of cold & hot water meters from small domestic type installations to large commercial and industrial properties.

The connections which come with the meters vary with the meter size & type, but connections are available to be added for all sizes for pulsed output, MBUS etc.

- **Compliance** - MID Approved, WRAS Approved
- **Communication Outputs Available** - Pulsed, MBUS, Wireless MBUS
- **Temperature** - Cold & Hot Types Available
- **Connection Size** - 15mm – 300mm

PIR Sensor



A range of low cost PIR Sensors for surface, flush and wall mounting.

There are switched live and volt free output variants. The light level can be switched off if required. Mains and low voltage variants.
Features

- Low cost solution
- Flush, surface or wall mounted
- Adjustable timer
- Optional switched live or volt free outputs

Major Water Leak System

The Merlin WDP is a water leak monitoring system that has been specifically designed to help achieve the requirements of 2018: 1.0 BREEAM UK New construction (non-domestic buildings).

The WDP system will allow designers, M&E contractors and developers to achieve the 'Credit' available to reduce the impact of water leaks that may otherwise go undetected. All the leak detection water meters and solenoid valves are WRAS-approved.

The system is designed to monitor water flowing through a pulse water meter. If the volume of water reaches the pre-set limit (customer adjustable) the system can isolate the mains water pipe, therefore limiting the amount of water and leak damage.



- Achieves one credit from BREEAM WAT 03
- Timer & programmable clock built in
- Two stage monitoring for occupied and unoccupied buildings
- BMS output available
- 2 zone input for reading 2x water meters (boundary and incoming)
- Volt free normally closed input for emergency stop buttons, fire alarm & security systems
- Remote sounder strobe output
- 230VAC & 24VDC outputs for water solenoid valves


Merlin Water Check

The Merlin Water Check is a combined water leak monitoring system for flow monitoring and point leak detection, designed to help achieve the requirements of 2018: 1.0 BREEAM UK New construction (non-domestic buildings) and to help reduce the risk of damage to property for insurance purposes.

- Combined flow monitoring & point leak detection
- Automatic water shut off as standard
- Various programmable settings dependent on occupancy
- Automatic holiday mode protection
- Audible & visual indication
- Insurance tariffs can be significantly reduced if permanent water leak detection is installed. Aviva, Zurich, More Than and other insurance companies all recommend water leak detection for residential properties.



Water Leak Monitor



The Merlin WLM system is the new S&S Northern Ltd permanent water leak detection system aimed towards commercial properties and residential apartment blocks. The Merlin WLM can be used standalone or part of a larger multi-zone detection system and comes with a clear LED status display.

- BMS Communications
- Strobe Alarm Outputs
- Control Panel Connectivity
- Fault Detection
- Electronic Valve Control
- SMS Alerting (With Additional Product)

WLMCP

Water Leak Puck / Probe



The WLMCP is designed to identify water leaks, either at specific points or in larger areas. The puck/probe can be rotated on the mounting bracket and secured in place with a wing nut. The WLMCP puck/probe should be utilized with the WLM and should not be directly linked to a BMS controller. The cable excitation employed is an isolated AC signal, ensuring that the detector cable remains unaffected by oxidation or erosion over time. This helps prevent the degradation issues associated with DC systems.

- WLMCP is easy to lay and detects along its entire length
- More than one WLMCP can be connected to a WLM
- Detects water leaks under floors or isolated plant rooms
- Designed to avoid false alarms caused by condensation or high humidity
- Used with the WLM

WLMC

2 Core Pre-Defined Length Water Leak Cable

The WLM 2 core sensing cables are capable of detecting the presence of water at any point along their length. When coupled with a WLM system, the cable swiftly identifies water intrusion and activates an alarm. The WLM 2 core is offered in various lengths to cater to specific coverage requirements, including custom pre-defined upon request.

The WLMC sensing cable is well-suited for a diverse range of applications, including data center sub-floors, telecommunication rooms, HVAC equipment locations, pipes, electrical vaults, storage areas, tanks, and roofs. Its compact, lightweight, and flexible design ensures straightforward installation. Additionally, the smooth construction allows for a rapid drying process.

- Identifies water presence along its entire length
- 2 core tape designed for water leak detection
- The WLMC cable is compact yet robust, displaying high resistance to abrasion and corrosion
- Features a sleek design that facilitates quick drying
- Comes in factory-terminated lengths, available in 2M, 5M, 10M, 15M & 25M
- Custom pre-defined lengths available upon request
- Used with the WLM



WLMFC

4 Core Length Water Leak Cable With Fault Detection

The WLM 4 core sensing cables are capable of detecting the presence of water at any point along their length. When coupled with a Merlin WLM system, the cable swiftly identifies water intrusion and activates an alarm. The 4 core cable includes fault detection, indicating incorrect wiring or a faulty cable, offered in various lengths to cater to specific coverage requirements. Supplied with pre-installed plastic connectors that seamlessly plug together, the WLMFC sensing cable is well-suited for a diverse range of applications, including plant rooms, data center sub-floors, telecommunication rooms, HVAC equipment locations, pipes, electrical vaults, storage areas, tanks, and roofs. Its compact, lightweight, and flexible design ensures straightforward installation. Additionally, the smooth construction allows for a rapid drying process.

- Identifies water presence along its entire length
- 4 core tape designed for water leak detection
- Includes fault detection, indicating incorrect wiring or faulty cable
- The WLMFC cable is compact yet robust, displaying high resistance to abrasion and corrosion
- Features a sleek design that facilitates quick drying
- Comes in factory-terminated lengths with pre-installed connectors, available in 5M, 10M, 20M, 50M & 100M
- Lead wire not included
- Used with the WLM





Ancillaries

PAGES
48-59



FAB-1 Fire Alarm bypass



Merlin
GDP2
Page 29

Merlin
1000BH
Page 28

OFTEN
USED
WITH

The Merlin FAB1 can be integrated with any of the Merlin suite of products to give the operator the opportunity to temporarily bypass the gas isolation system. With prior notice to a fire alarm test, the operator can turn the key to the on position giving an uninterrupted gas supply for between 10 and 45 minutes.

During this time the system controlling the gas will ignore shut-off signals from the buildings fire alarm system and allow factors such as heating systems to remain operational. The bypass time can be adjusted using the blue switches inside the panel. During the bypass time gas can still be shut off, pressing the emergency gas shut off button will close the gas solenoid valve.

OFTEN
USED
WITH

Merlin
GDP2X
Page 27

Merlin
1000BH
Page 28

Merlin
GDP2
Page 29

Merlin
GDPX+
Page 26

The fusible link is most commonly used in a boiler room application. These are fitted as a means of fire protection, if the boiler room temperature reaches over 72 degrees then the fusible wire inside will melt and therefore send an electronic signal to isolate the gas supply. Multiple fusible links can be fitted in one area.

Fusible Link



Emergency Stop



Merlin
2000X
Page 11

Merlin
3000S
Page 6

Merlin
1000VW+
Page 20

OFTEN
USED
WITH

The Emergency Stop button is used to isolate the gas supply into an area in the event of emergency.

The button is fitted with a Perspex screen which should be pressed to activate, and then can be reset using a key (supplied with every emergency knock-off button). This button can be linked with any Merlin gas safety system to give various means of isolation within an area.

OFTEN
USED
WITH

Merlin
GDP2X
Page 27

Merlin
GDPX+
Page 26

Merlin
GDP2
Page 29

The Sounder Alarm Beacon is a remote alarm beacon most commonly used outside a boiler room. This sounder alarm beacon can give both an audible and visual alarm in the event of an emergency. Various colours are available to suit the application.

Sounder Alarm Beacon



Air Pressure Differential Switch

Merlin
CT1200S
Page 10

Merlin
1000V
Page 22

OFTEN
USED
WITH



An air pressure differential switch is a mechanical switch fitted in ductwork which can be used to monitor and check airflow rates. These switches are adjustable and have a range from 20-300PA, they also come with a 1m duct kit to be fitted into the ductwork and detect the airflow.

Water Solenoid Valve

OFTEN
USED
WITH

Merlin
1000VW+
Page 20



Our water solenoid valves are most commonly found in science laboratories where the teachers want full control of the water supply to the benches, but they can be used in a range of applications.

Similar to a gas solenoid valve, our water solenoid valves are normally closed, auto-reset and 230V so they can be controlled by the Merlin gas safety systems.

Once again, we have a full range of sizes available, WRAS approved and can offer specialist types on request.

Gas Solenoid Valve

Merlin
1000BH
Page 28

Merlin
1000V
Page 22

Merlin
2000X
Page 11

OFTEN
USED
WITH



Our gas solenoid valves are 230V powered, normally closed, auto-reset and will most commonly be powered from our Merlin gas safety systems. In the event of an emergency, the Merlin gas safety system will take power away from the gas solenoid valve causing it to slam shut, and when power is re-instated this will then allow gas to flow through the pipework.

We have a full range of sizes available, both screwed and flanged, and can offer specialist gas valves on request.

Pressure Transducer

OFTEN
USED
WITH

Merlin
GDPX+
Page 26

Merlin
1000V
Page 22

Merlin
2000X
Page 11



A transmitter used to check for leaks in the gas line, by detecting pressure drops from the downstream port of the gas solenoid valve.

DPM2

Merlin 2000X Page 11
 Merlin 1000V Page 22
 Merlin 1000BH Page 28

OFTEN USED WITH

The DPM-2 is a dual pressure monitor which enables connection of two gas solenoid valves and two pressure sensors to any Merlin gas proving panels.



CS1/CS2

OFTEN USED WITH

Merlin CT1200S Page 10
 Merlin 1000V Page 22
 Merlin CT1650+ Page 8

The Merlin CS1 & CS2 Current Switch is to be used in conjunction with the Merlin range of ventilation interlock systems and can be used as an alternative to air pressure differential switches.



PM2+

Merlin 2000S Page 11
 Merlin 1000V Page 22
 Merlin CT1750+ Page 7

OFTEN USED WITH

The Merlin PM2+ Current Monitor is a dual fan current monitor and is to be used in conjunction with the Merlin systems: the unit can be used as an alternative to an air pressure differential switch.




OFTEN USED WITH

Merlin 3000S Page 6

The Optical Sensor emits a beam across the kitchen canopy, if the beam is interrupted by excess smoke/steam it will send a signal back to the control panel.

Optical Sensor



Duct Thermostat



Merlin
3000S
Page 6

OFTEN
USED
WITH

The Duct Thermostat provides a control signal back to the Merlin control panel depending on the temperature in the duct work.

As the duct temperature becomes too hot the Merlin control system can increase ventilation.

Inverter



S&S Northern Ltd offer a large range of invertors for use with our Merlin control panels, ventilation units & industrial pumps.

Our invertors are available in single phase & three phase and cover a range from 0.75KW up to 24KW so suitable from the smallest kitchen fan to very large industrial pumps.

Speed Controller


We stock a full range Electronic fan speed controllers. This range of fan speed controllers can be used with most Fans / Motors which is single phase – 240 volts and fan speed controllable using either 2 or 3 wire control.



Gas Meter

We offer gas meters to cover all domestic & commercial buildings from ¼" diaphragm gas meters, up to 6" inline quantometers.

Our gas meters come with a range of outputs, most commonly a pulsed output but there is the option for other communications such as MODBUS, MBUS etc.



Water Meter



S&S offer a large range of cold water meters & hot water meters from small domestic type installations to large commercial and industrial properties.

The connections which come with the meters vary with the meter size & type, but connections are available to be added for all sizes for pulsed output, MBUS etc.

- **Compliance** -
MID Approved, WRAS Approved
- **Communication Outputs Available** -
Pulsed, MBUS, Wireless MBUS
- **Temperature** -
Cold & Hot
- **Connection Size** -
15mm – 300mm

Heat Meter



As part of our metering range, we are also able to offer heat meters for domestic & commercial premises. These are available using both inline and clamp-on types and come with a range of communications available as standard.

Gas Solenoid Valve CPI Switch

The closed position switch can be used on Goldseal gas solenoid valves to indicate position of the valve

Type Numbers

CPI-20/25 for valve size 3/4" & 1"
CPI-32/40 for valve sizes 1.1/4" & 1.1/2"
CPI-50 for valve size 2"
CPI-65/80 for valve size 2.1/2" & 3" BSP & Flanged
CPI-100 for valve size 4" Flanged



Bump Test Kit

We offer a full range of bottled test gases and testing equipment. The Bump kits are used to check and maintain gas detectors.

- Carbon Monoxide
 - Methane
 - LPG
 - Nitrogen
- Others available on request



Indoor Air Quality

S&S Northern have a wide a range of indoor air quality sensors including carbon dioxide, temperature, humidity, PM1, PM2.5, PM10, VOCs and VRF refrigerant leak detection.



PAGES
60-65



Merlin RS Range

Carbon Dioxide, Temperature & Humidity Sensors



Monitor and measure carbon dioxide (CO2), temperature and relative humidity. Designed for all areas being directly connected to low or mains voltage supply, e.g., residential, public, commercial, and light industrial environments.

- Analog: 3x 0-10V signals for CO2 (PPM), Temperature (°C) and Humidity (% Relative).
- Digital RS-485: Modbus RTU or BACnet MS/TP communication protocols.
- VFC Relay (CO2): 1x SPST 70mA Max.
- Thermistor output for 3rd party temperature monitoring.
- Blank, LED or Display Screen available.

Excellent stability and strong anti-interference, long-life sensors. Fully calibrated. IGEM/UP/11. BS 50543. Harmonised BS 61010-1 & BS 50270. 3 year warranty.

Designed & Manufactured in the UK

90
models available

3 year warranty



Merlin IAQ Monitor

Carbon Dioxide, Temperature & Humidity, PM1, PM2.5, PM10 & VOCs



Monitor and measure carbon dioxide (CO2), temperature, dust (PM), volatile compounds (VOCs) and relative humidity. Designed for all areas being directly connected to mains or low 24v AC or DC voltage supply, e.g., residential, public, commercial, and light industrial environments, which support a Digital RS-485: Modbus RTU or BACnet MS/TP communication protocols.

- Digital RS-485: Modbus RTU or BACnet MS/TP communication protocols.
- 24V AC/DC or 110-240V AC
- Blank, LED or Display Screen available.

Excellent stability and strong anti-interference, long-life sensors. Fully calibrated. IGEM/UP/11. BS 50543. Harmonised BS 61010-1 & BS 50270. 3 year warranty.

Designed & Manufactured in the UK

12
models available

3 year warranty



Merlin RG Range

VRF Refrigerant Gas Leak Detectors




Designed for all areas utilizing variable refrigerant flow in excess of the EN378, F Gas Directive & BREEAM guidelines whereby the additional protection of a VRF detector is advisable.

- Analog: 1x 0-10V signals for Refrigerants (PPM).
- Digital RS-485: Modbus RTU or BACnet MS/TP communication protocols.
- Thermistor output for 3rd party temperature monitoring.
- Over 40+ Refrigerant gases available
- Excellent stability and strong anti-interference, long-life sensors.
- Fully calibrated.
- Designed & Manufactured in the UK
- Standard 3 year manufacturers warranty.
- In-Built Audible Alarm
- Visual LED for Alarm Status (Aailable on LED version only)


Designed & Manufactured in the UK

40+
refrigerants available


3 year warranty



Occupiable rooms in offices.



Occupiable rooms for aerobic exercise such as sports halls and gymnasiums.



Occupiable rooms where members of the public are likely to gather.

Digital RS-485: Modbus RTU or BACnet MS/TP communication protocols.



Excellent stability and strong anti-interference, long-life sensors. Fully calibrated. IGEM/UP/11 compliant. BS 50543 requirements applied. Harmonised BS 61010-1 & BS 50270.



Spec Wizard

www.snsnorthern.com/spec-wizard/

Ensure your project has the correct equipment

Here at S&S Northern we ensure your project is meeting all the latest gas regulations and recommendations.

As part of our dedication to continual progress and development, the S&S Northern team has developed the pioneering Spec Wizard. Spec Wizard is a dynamic resource that significantly reduces a consultant's workload by searching for and identifying the most appropriate equipment for a project, location or specification.

By simply answering questions from the drop down menu, Spec Wizard will instantly generate the ideal specification a consultant needs to meet various gas regulations on their project.

Spec Wizard will then create and email an equipment list which can then be directly used within a specification document, saving hours of time and money during the research and sourcing stages.

For help with the Spec Wizard or if you would like one of S&S Northern's technically trained sales engineers to explain the process over the telephone, please call us on +44 (0) 1257 470 983

Book Your Free CIBSE Accredited Webinar

Do your projects include Boiler/PlantRooms? Laboratories? Commercial kitchens? Receive up to date knowledge of Gas Safety Regulations.



Two CPD Sessions

CPD 1

Gas Safety Guidelines
For Commercial
Buildings

- ✓ **CO2 Monitoring in schools & classrooms – ASHRAE / REVHA / CIBSE Guidance / DFE Guidance**
- ✓ **Gas Safety in School Boiler Houses / Plant Rooms – BS6644 & BB101**
- ✓ **Gas Safety & Utility Control with Science Classrooms – IGEM/ UP11**
- ✓ **Energy Saving & Demand Controlled Ventilation – DW172 & BS6173**

CPD 2

Monitoring, Metering &
Detection For
Commercial Buildings

- ✓ **Major Water Leak Detection (BREEAM WAT 03)**
- ✓ **Water Monitoring (BREEAM WAT 02)**
- ✓ **Part L – 2022 Update (Monitoring & Sub-Metering)**
- ✓ **BREEAM HEA02 – Energy Saving & Indoor Air Quality**

Safety Regulations

The Safety Regulations Our Panels Are Designed To Exceed

Commercial Kitchens Refer to pages 8-15

BS 6173:2020

- "Appliances shall be interlocked with any mechanical ventilation system that is fitted to enable their safe operation."
- "An interlock shall be provided which will cut off the gas supply or prevent the operation of appliances if the mechanical ventilation system provides an inadequate airflow rate for the safe operation of appliances and the safety of personnel."
- "An interlock on a new installation shall not be fitted with an override function."
- "Only detectors designed to operate in a commercial catering environment shall be installed. They shall give an audible alarm and be linked with an automatic gas shut-off system which is fail-safe and requires manual intervention to restore the gas supply."

IGEM UP19

- "Actuation of an alarm when the CO2 level is above 2800ppm shall cause a visual or audible warning to occur. If the CO2 level rises above 5000ppm, any interlock shall cause lockout of the gas system to occur"
- "In accordance with BS6173 over-rides to interlocks and interlock systems are not permitted and, as appropriate the responsible person shall be advised accordingly including within any written report."
- "CO2 Monitoring alone is not acceptable as the main interlock for Type B appliances but may be used in conjunction with air flow, air pressure or fan power monitoring"
- "When a demand controlled or variable speed system is installed an environmental sensor such as a CO2, steam or temperature sensor shall be included as part of the gas interlock requirements specified in clause 5.2.1.1 and clause 5.2.1.2 or clause 5.2.1.3."

Education Buildings Refer to pages 16-23

IGEM UP11

- "Where an AIV is required the system shall include a downstream integrity check before can be re-opened."
- "Such automatic means of isolation shall, in the event of a shutdown, require manual re-setting to take place such that check is performed to prove that all the downstream gas isolation valves are closed."
- "High levels of CO2 shall cause an alarm at 2800ppm and shut down of gas supply at 5000ppm."

BB101

- "CO2 levels should be measured at seated head height in all teaching and learning spaces."
- "Where only Type A appliances are used, interlocking may be achieved by environmental monitoring of carbon dioxide as described in IGEM UP 19."
- "When practical activities are not taking place and gas is not in use the ventilation in practical spaces should be controlled to meet the normal CO2 levels for teaching and learning spaces as described in section 2.4."
- "In these practical spaces, higher levels of CO2 are acceptable for the periods of time when Bunsen burners, cookers and other gas-fired appliances are in use as described in section 2.9"

BREEAM & Water Leak Detection Refer to pages 42-45

BREEAM WAT 02

- The aim of BREEAM WAT 02 is to ensure water consumption can be monitored and managed and therefore encourage reductions in water consumption offering one credit.

BREEAM WAT 03

- BREEAM WAT 03 offers two credits in total both based around major water leak detection & water leak prevention.

Boiler / Plant Rooms Refer to pages 24-31

BB100

- "A means of automatically shutting off the fuel supply in the event of a fire. This should include an emergency shut-off push-button at the entrance to the boiler room."
- "In the event of a genuine alarm, the system should require manual resetting, but if it is purely a power failure and appropriate self-proving devices are in place, then automatic resetting is appropriate to prevent the risk of pipe freezing during weekends or holiday periods."
- "In addition, a carbon monoxide or carbon dioxide detection system is often required in boiler/plant rooms for all fuel types, particularly where a boiler/plant room forms part of the school building."
- "The detection system should both raise an alarm and isolate the fuel supply."

IGEM UP/2

- "In the event of a genuine alarm, the system should require manual resetting, but if it is purely a power failure and appropriate self-proving devices are in place, then automatic resetting is appropriate to prevent the risk of pipe freezing during weekends or holiday periods."
- "A means of automatically shutting off the fuel supply in the event of a fire. This should include an emergency shut-off push-button at the entrance to the boiler room."
- "In addition, a carbon monoxide or carbon dioxide detection system is often required in boiler/plant rooms for all fuel types, particularly where a boiler/plant room forms part of the school building."
- "The detection system should both raise an alarm and isolate the fuel supply."

CO2 Monitoring Refer to pages 32-41

Part F - June 2022

- 1.21 In new buildings, the following types of occupiable rooms, unless they are rooms of the size described in paragraph 1.22, should have a means of monitoring the indoor air quality. This may be achieved using CO2 monitors or other means of measuring indoor air quality:
 - Occupiable rooms in offices.
 - Occupiable rooms where singing, loud speech or aerobic exercise or other aerosol generating activities are likely to take place. These may include rooms, for example, in gymnasiums, other indoor sports venues, dance studios, theatres, concert halls, public houses, nightclubs, places of assembly, as well as in other types of building.
 - Occupiable rooms where members of the public are likely to gather. These may include rooms, for example, in public buildings, hotels, gymnasiums, indoor sports venues, dance studios, theatres, concert halls, public houses, nightclubs, places of assembly, as well as in other type of building.
 - Occupiable rooms which are maintained at both low temperatures and low levels of humidity. These may include rooms used for chilled food processing and occupied cold stores.
- 1.22 The guidance in paragraph 1.21 does not apply to the following sizes of room. a. Small spaces up to 125m³ volume, or 50m² floor area. b. Large spaces over 800m³ in volume, or 320m² floor area. 1.23 Where CO2 monitors are used, they should meet all of the following:
 - Be non-dispersive infrared (NDIR) type CO2 monitors.
 - Be mains powered.
 - Be placed at breathing height and away from windows, doors or ventilation openings where practicable.
 - Be placed at least 500mm from people where practicable.

Head Office

S&S Northern Ltd
Wallace Francis House
Barnes Wallis Way
Buckshaw Village
Chorley
Lancashire
PR7 7JN

T +44 (0) 1257 470 983
E info@snsnorthern.com

